



SECTION I: PRODUCT INFORMATION

PRODUCT: **Sika® Primer-206 G+P**

REVISION DATE: February 15, 2009

USAGE: ADHESIVE/SEALANT PRIMER

MANUFACTURER: SIKA CANADA INC.
601, avenue Delmar
Pointe Claire, QC
H9R 4A9**EMERGENCY TELEPHONE NUMBER: CANUTEC (collect) (613) 996-6666**

TDG CLASSIFICATION: Resin solution, flammable

WHMIS Classification: B2, D2A, D2B

UN NUMBER: 1866

Class: 3

Packaging Group: II

SECTION II: HAZARDOUS INGREDIENTS

Hazardous ingredients	%	T.L.V.	# CAS	LD ₅₀ (mg/kg) (species, route)	LC ₅₀ (species, route)
Hexamethylene 1,6-Diisocyanate homopolymer	10-30	Not Established	28182-81-2	Not Established	Not Established
ETHYL ACETATE	30-60	400ppm	141-78-6	5600 (oral, rat)	19600 ppm/4 hours (rat)
XYLENE	1-5	100ppm	1330-20-7	4300 (oral, rat)	6350ppmh/4H
CARBON BLACK	5-10	3.5 mg/m ³	1333-86-4	15 400 mg/kg (oral, rat)	Not Available

SECTION III: PHYSICAL CHARACTERISTICS

Physical State: Liquid
Appearance and Odor: Mild odor black liquid

Odor Threshold: Not Established
Evaporation Rate: 6 (ethyl acetate)
Vapor Density: 3.0 (Ethyl acetate/ air = 1)
Vapor Pressure: 76 mm Hg (Ethyl acetate / 20c)Boiling Point: 77°C (Ethyl acetate)
Freezing Point: - 83°C (Ethyl acetate)
Density: 0,9 g/ml
Water Solubility: 87 g/l (Ethyl acetate)
pH: Not Established
% volatile: < 75
Water/Oil Distribution: 0.2 (Ethyl acetate)



PRODUCT: **Sika® Primer-206 G+P**

SECTION IV: FIRE AND EXPLOSION HAZARDS

<p>Flammability: Yes</p> <p>If Yes, under what conditions: Flame, spark. Vapors can create an explosive, air reacting mixture. Vapors are heavier than air and may accumulate in enclosed area</p> <p>Extinguishing methods: Foam, dry chemical products, CO₂, water for large flames.</p> <p>Special Methods: Firefighters must wear complete protective clothing with a self-contained breathing apparatus.</p>	<p>TDG inflammability Class: 3</p> <p>Flammable upper limits (% vol.): 11.5 Ethyl acetate</p> <p>Flammable lower limits (% vol.): 2.0 Ethyl acetate</p> <p>Flash Point (method used): > -4°C (TCC)</p> <p>Auto-ignition temperature: 426°C Ethyl acetate</p> <p>Dangerous Combustion Products: Carbon oxides, ketone, aldehyde, HDI, Nitrogen Oxide, Hydrogen cyanide</p> <p>Protect from mechanical impact: No</p> <p>Protect from static discharge: Yes</p>
--	--

SECTION V: REACTIVITY DATA

<p>Chemical stability: Yes</p> <p>If not, under what conditions</p> <p>Incompatibility with other material: Yes</p> <p>If Yes, which ones: Strong acid, strong oxidizer, amine.</p>	<p>Dangerous decomposition products: Carbon oxides, Aldehydes, Ketones, Nitrogen Oxide, HDI</p> <p>Polymerization Risks: No</p>
---	---



PRODUCT: Sika® Primer-206 G+P

SECTION VI: TOXIC PROPERTIES

ROUTE OF ENTRY / CONTACT

Eyes: Irritating.

Skin: Irritating. Contact may result in dermatitis, allergic reactions, and sensitization. May cause skimming of skin's fat and drying of the skin.

Inhalation: Vapor or mist from this product may cause irritation. May cause a respiratory sensitization. May cause central nervous system depression.

Ingestion: May cause nausea, vomiting, fainting, diarrhea, G.I. system disorder, constipation, ulcers.

Over exposure may cause breathing difficulties, sensitization, headaches, nausea, vomiting, and blindness.

May aggravate respiratory, skin, eye, lung problems and allergies.

A person who is allergic to isocyanate may have a reaction with a level of isocyanate well below the T.L.V.

NOTE: Xylene is a central nervous system depressor and cause kidney and liver damage, in rare cases; it may cause a sensitization of the heart muscle causing arrhythmia.

Carcinogenicity: Carbon black is possibly carcinogen according the IARC

Toxic effects on reproduction: No

Teratogenicity: Xylene is Classified as a development toxicant (embryo toxin).

Mutagenicity: No

Product with synergistic effects: Ethyl acetate + formaldehyde, xylene + benzene, toluene or ethanol

A chronic exposure will increase the toxic effects mentioned in this section and may aggravate respiratory problems. An overexposure may cause death.



PRODUCT: Sika® Primer-206 G+P

SECTION VII: PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT

Gloves: Use chemical resistant gloves. (ex: Neoprene)

Respiratory equipment: A self-contained breathing apparatus or a positive feed is recommended when TLV can be exceeded

Eyes: Full-face mask or safety glasses

Shoes: Leather

Clothing: Rubber Apron

Other: Eye wash station, shower

OTHERS

Ventilation: Sufficient ventilation required

Procedure in case of leaks: Absorb with sand or other absorbent material. Avoid sparks and sources of ignition, sufficient ventilation is required

Handling and Equipment methods: Avoid skin, eye and clothing contact

Warehouse Requirements: Keep all containers closed in a cool, well ventilated, dry area. Keep away from heat and open flame.

Special Shipping Instructions: See TDG class

Waste disposal: Dispose of sand and rinse water according to municipal, provincial or federal laws for disposal of chemicals.



PRODUCT: Sika® Primer-206 G+P

SECTION VIII: FIRST AID

- Skin : Remove contaminated clothing and shoes.
Wash immediately with plenty of water.
Wash clothing before re-wearing.
Consult a physician if required.
- Eyes : Rinse eyes immediately with plenty of water for several minutes to ensure a proper wash. Keep eyelids open.
See a physician immediately.
- Inhalation : In the case of overexposure, evacuate to fresh air.
Consult a physician if required.
- Ingestion : Drink plenty of water. Do not induce vomiting.
Do not give anything by mouth to an unconscious person.
See a physician immediately.

SECTION IX: PREPARATION INFORMATION

Prepared by : Steve Gosselin
 Telephone # : (514) 697-2610
 Fax # : (514) 694-2792

Notice To Reader

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Technical Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this MSDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikacanada.com or 514-697-2610.