

Material Safety Data Sheet

according to HazCom 2012

SDS #: GM520

GM520

Issue Date 2015-02-23 Revision Date 2015-02-23 Version 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name GM520

Other means of identification

Product Code GM520 Synonyms Not applicable

Recommended use of the chemical and restrictions on use

Identified uses Adhesives.

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address Glass Mechanix Solutions

350 W. 2700 S.

Salt Lake City, UT 84115

Emergency Telephone Tel: 877-604-6509

2. HAZARDS IDENTIFICATION

Emergency Overview

Physical stateliquidColorcolorlessOdorCharacteristicAppearancetransparent

Classification

OSHA Regulatory Status

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Specific target organ toxicity (single exposure)	Category 3

Target Organ Effects

Respiratory system, EYES, Skin.

GHS Label elements, including precautionary statements



GM520

Signal word

Warning

Hazard statements

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H335 - May cause respiratory irritation

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves/protective clothing/eye protection/face protection

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing should not be allowed out of the workplace

Use only outdoors or in a well-ventilated area

Precautionary Statements - Response

IF exposed or concerned, get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN: Wash with plenty of soap and water, Take off contaminated clothing and wash before reuse, If skin irritation or rash occurs: Get medical advice/attention.

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

IF SWALLOWED Get medical advice/attention if you feel unwell

Collect spillage.

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant.

Hazards not otherwise classified (HNOC)

None

Other Information

May be harmful if swallowed May be harmful in contact with skin

Unknown acute toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Hazardous

Chemical Name	CAS No	Weight-%	Trade Secret	Classification (Reg. 1272/2008)
Isobornyl Acrylate	5888-33-5	30 - 60	*	STOT SE 3 (H335) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Aquatic Chronic 2 (H411)
2-Hydroxyethyl methacrylate	868-77-9	10 - 30	*	Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Skin Sens. 1 (H317)
Acrylic acid	79-10-7	1 - 5	*	Flam. Liq. 3 (H226) Acute Tox. 4 (H302) Acute Tox. 4 (H312) Acute Tox. 4 (H332) Skin Corr. 1A (H314) Aquatic Acute 1 (H400)

GM520

Issue Date 2015-02-23 Revision Date 2015-02-23 Version 1

Silane Coupling Agent	Proprietary	1 - 5	*	STOT SE 3 (H335) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319)
-----------------------	-------------	-------	---	---

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures

General advice

IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.

Eye contact

Flush eyes with water at least 15 minutes, get medical attention if eye irritation develops or persists.

Skin Contact

Wash off immediately with plenty of water, Get medical attention if irritation develops and persists.

Inhalation

Move to fresh air, If symptoms persist, call a physician.

Ingestion

If swallowed, Rinse mouth, Get medical attention.

Self-protection of the first aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed

Main Symptoms

No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use CO2, dry chemical, or foam.

Unsuitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

Hazardous combustion products

Hazardous decomposition products due to incomplete combustion.

Explosion data

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Page 2

GM520

Issue Date 2015-02-23 Revision Date 2015-02-23 Version 1

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Ensure adequate ventilation, Wear protective gloves/clothing and eye/face protection.

Environmental precautions

Environmental precautions

Do not allow material to contaminate ground water system, Try to prevent the material from entering drains or water courses, See Section 12 for additional Ecological Information, Local authorities should be advised if significant spillages cannot be contained.

Methods and material for containment and cleaning up

Methods for containment

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Handle in accordance with good industrial hygiene and safety practice, Ensure adequate ventilation, Protect from light.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions

Keep container tightly closed in a dry and well-ventilated place, Protect from light.

Incompatible products

Amines, Strong oxidizing agents, Strong acids, Strong bases, Oxygen scavengers, Thiosulfates.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acrylic acid	TWA: 2 ppm S*	(vacated) TWA: 10 ppm (vacated) TWA: 30 mg/m³ S*	TWA: 2 ppm TWA: 6 mg/m³

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

TLV - Threshold Limit Value

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

PEL - Permissible Exposure Limits

NIOSH IDLH

Immediately Dangerous to Life or Health

Appropriate engineering controls

Engineering Measures

Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

GM520

Issue Date 2015-02-23 Revision Date 2015-02-23 Version 1

Individual protection measures, such as personal protective equipment

Eye/face protection

Safety glasses with side-shields, If splashes are likely to occur, wear:, Goggles.

Skin and body protection

Wear suitable protective clothing.

Respiratory protection

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required

Hygiene measures

When using, do not eat, drink or smoke, Handle in accordance with good industrial hygiene and safety practice, Wear suitable gloves and eye/face protection, Wash hands before breaks and at the end of workday, Avoid breathing vapors, mist or gas, Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	liquid		
Appearance	transparent	Odor	Characteristic
Color	colorless	Odor threshold	No information available

<u>Property</u> pH Melting point/freezing point	<u>Values</u>	Remarks / • Method No information available No information available
Boiling point / boiling range		No information available
Flash point	108 °C / 226 °F	
Evaporation rate		No information available
Flammability (solid, gas)		No information available
Flammability Limit in Air		

Upper flammability limit Lower flammability limit Vapor pressure No information available
Vapor density No information available

Specific GravityNo information availableWater Solubility VALUENo information availableSolubility in other solventsNo information availablePartition coefficient: n-octanol/waterNo information availableAutoignition temperatureNo information available

Autoignition temperatureNo information availableDecomposition temperatureNo information availableDynamic viscosity

Kinematic viscosity

No information available

Explosive propertiesNo information available
No information available

Other Information

Softening point
VOC Content (%)
Density
Bulk density
No information available
No information available
No information available
No information available

10. STABILITY AND REACTIVITY

Reactivity

No information available

D.

GM520

Issue Date 2015-02-23 Revision Date 2015-02-23 Version 1

Chemical stability

Stable under normal conditions.

Possibility of Hazardous Reactions

Hazardous polymerization

None under normal processing.

Conditions to avoid

Protect from light. Heat, flames and sparks.

Incompatible materials

Amines, Strong oxidizing agents, Strong acids, Strong bases, Oxygen scavengers.

Hazardous Decomposition Products

No decomposition if stored and applied as directed.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

No acute toxicity information is available for this product

InhalationThere is no data available for this productEye contactThere is no data available for this productSkin ContactThere is no data available for this productIngestionThere is no data available for this product

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Isobornyl Acrylate	= 4890 mg/kg (Rat)	> 5 g/kg(Rabbit)	
2-Hydroxyethyl methacrylate	= 5050 mg/kg (Rat)	> 3000 mg/kg(Rabbit)	
Acrylic acid	= 33500 µg/kg (Rat)	= 280 μL/kg(Rabbit)	= 5300 mg/m ³ (Rat) 2 h
Silane Coupling Agent	> 5000 mg/kg (Rat)		

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization May cause sensitization of susceptible persons.

Mutagenic effectsNo information available.Reproductive toxicityNo information available.

Carcinogenicity Contains no ingredients above reportable quantities listed as a carcinogen.

Legend

STOT - single exposure
STOT - repeated exposure
Target Organ Effects
No information available.
No information available.
Respiratory system, EYES, Skin.

Chronic toxicity Repeated contact may cause allergic reactions in very susceptible persons

Avoid repeated exposure

Aspiration hazard No information available.

Numerical measures of toxicity - Product Information

Unknown acute toxicity 0% of the mixture consists of ingredient(s) of unknown toxicity

GM520

The following values are calculated based on chapter 3.1 of the GHS document.

ATEmix (oral) 4020 mg/kg ATEmix (dermal) 4614 mg/kg ATEmix (inhalation-dust/mist) 9.5 mg/l

12 ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects

2.3% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Acute aquatic toxicity

Product Information

Environmental product testing for acute and chronic aquatic effects determined classification to be Category 3

Component Information

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates
Isobornyl Acrylate	ErC 50 = 2.7 mg/L 96 h (Pseudokirchneriella subcapitata)	LC50 = 1.8 mg/L 96 h (Danio rerio)	EC 50 = 1.1 mg/L 48 h (Daphnia magna)
2-Hydroxyethyl methacrylate		LC50 = 227 mg/L 96 h (Pimephales promelas)	EC50 > 380 mg/l 48 h (Daphnia magna)
Acrylic acid	EC50 0.04 mg/L 72 h (Desmodesmus subspicatus)	LC50 = 222 mg/L 96 h (Brachydanio rerio)	EC50 = 95 mg/L 48 h
Silane Coupling Agent	EC50 > 536,00 mg/l 72 h (Scenedesmus subspicatus)	LC50 > 1024,00 mg/l 96 h (Brachydanio rerio)	EC50 > 876,00 mg/l 48 h (Daphnia magna)

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

Chemical Name	log Pow
2-Hydroxyethyl methacrylate	0.47
Acrylic acid	0.46

Other adverse effects

None

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste Disposal Methods

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated packaging

Dispose of in accordance with local regulations.

14. TRANSPORT INFORMATION

GM520

<u>DOT</u> Not regulated

ICAO/IATA Not regulated

IMDG/IMO Not regulated

15. REGULATORY INFORMATION

International Inventories

Complies **TSCA AICS** Complies DSL/NDSL Complies **EINECS/ELINCS** Complies Complies **ENCS IECSC** Complies **KECL** Complies Complies **NZIoC** Complies **PICCS** Complies **ECSI**

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

AICS - Australian Inventory of Chemical Substances

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

PICCS - Philippines Inventory of Chemicals and Chemical Substances

ECSI - Taiwan Existing Substance Inventory

US Federal Regulations

OSHA Regulatory Status

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	SARA 313 - Threshold Values %
Acrylic acid	1.0

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Acrylic acid	5000 lb		RQ 5000 lb final RQ
THE SECOND SECON	and the second of the second o		RQ 2270 kg final RQ

GM520

Issue Date 2015-02-23 Revision Date 2015-02-23 Version 1

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Acrylic acid	Χ	X	X

16. OTHER INFORMATION

Prepared By **EHS** Department **Revision Date** 2015-02-23

No information available **Revision Note**

Disclaimer

This information is furnished without warranty, express or implied. This information is believed to be accurate to the best knowledge of Glass Mechanix Solutions and its subsidiaries and affiliates (Glass Mechanix Solutions). The information in this SDS relates only to the specific material designated herein. Glass Mechanix Solutions assumes no legal responsibility for use of or reliance upon the information in this SDS.

end