



MATERIAL SAFETY DATA SHEETS

SECTION 1 : CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name : SILVERWAX 48 - CORRECTION POLISH
Chemical name and synonyms : applicable (mixture)
Manufacturer : Laboratoire Hygienex Inc. **Supplier :** Same
Address : 6400 Zephirin-Paquet **Address :** Same
 Québec (Québec)
 Canada G2C0M3
Telephone : 1-418-522-2332 **Telephone :** Same
Emergency phone (CANUTEC) : (613) 996-6666 Laboratoire
Issue by : Hygienex Inc.
Product use : Car care (Industrial/Institutional)

HMIS : Santé : 2 Inflammabilité : 2 Réactivité : 0 Protection Personnelle : B

SECTION 2 : COMPOSITION/INFORMATION ON INGREDIENTS

| Ingrédient | CAS | % p/p |
|--|------------|-------|
| Water | 7732-18-5 | 30-60 |
| Aluminium oxide | 1344-28-1 | 10-30 |
| Hydrotreated light petroleum distillat | 64742-47-8 | 5-15 |
| White mineral oil (petroleum) | 8042-47-5 | 1-5 |

SECTION 3 : HAZARDS IDENTIFICATION

Eyes contact : Direct contact may cause irritation, redness and pain.
Skin contact : May cause skin irritation. May be absorbed through the skin with possible systemic effects.
Inhalation : May cause dizziness and euphoria leading to unconsciousness in severe cases. Vapors also irritate the respiratory tract. Symptoms may include coughing, difficult breathing and chest pain.
Oral : Ingestion may cause burning of mouth, throat, and stomach with abdominal pain, nausea, diarrhea, headache and dizziness.

Effects of repeated overexposure

| | |
|-----------------------------|--|
| Skin : | Prolonged or repeated exposure may cause skin irritation, even skin dryness. |
| Inhalation : | May cause liver, kidney or central nervous system damage after repeated or prolonged exposures. |
| Oral : | Cause burning of mouth, throat, and stomach with abdominal pain, nausea, diarrhea, headache and dizziness. |
| Primary route of exposure : | Skin contact, eye contact, inhalation and swallowing are the primary routes of exposure to this product. |

The above listed potential effects of overexposure are base on actual data, results of studies performed upon similar compositions, component data, and/or expert review of the product. Please refer to section 11 for detailed toxicology information.

SECTION 4 : FIRST-AID MEASURES

| | |
|-----------------------|---|
| Eyes contact : | Flush eyes gently with water for at least 15 minutes while holding eyelids apart. |
| Skin contact : | In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Seek medical attention if problem persist. |
| Inhalation : | Remove in fresh air. Seek medical attention if problem persist. |
| Swallowing : | Give water. Do not induce vomiting. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. If possible, do not leave individual unattended. Seek medical attention. |
| Notes to physicians : | Treat according to person's condition and specifics of exposure. |

SECTION 5 : FIRE-FIGHTING MEASURES

| | |
|--------------------------------------|---|
| T.D.G. Flammable class : | Class 3 |
| Flammability : | Yes |
| Flash point, closed cup (°C) : | 59 |
| Explosive limit temperature (°C) : | Not available |
| Autoignition temperature (°C) : | Not available |
| Lower flammable limit (% by vol.) : | Not available |
| Higher flammable limit (% by vol.) : | Not available |
| Sensitivity to static discharge: | Not available |
| Sensitivity to impact : | None |
| Hazardous Products of Combustion : | May form: carbon and nitrogen oxide. |
| Fire and Explosion Hazards : | Vapours form from this product and may travel or be moved by air currents and ignited by pilot lights, other flames, sparks, heaters, electrical equipment, static discharges or other ignition sources at locations distant from handling point. |
| Extinguishing Media : | Regular foam, water, carbon dioxide. |

Fire Fighting Instructions : Wear a self-contained breathing apparatus with a full face piece operated in the positive pressure. Refer to the personal protective equipment section of this MSDS.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

General information : Use proper personal protective equipment as indicated in Section 8. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

Small spill : Remove source of heat, sparks or flames. Absorb residue or small spills with absorbent material.

Large Spill : Stop leak if without risk. Provide adequate ventilation and protective equipment. Remove sources of heat, sparks or flames. Spill should be collected in suitable containers or absorbed on a suitable absorbent material for subsequent disposal.

Disposal measures : See Section 13.

SECTION 7 : HANDLING AND STORAGE

Handling : Keep away from heat, sparks, and open flame. Keep container closed when not use. Use adequate ventilation. Avoid breathing vapours. Avoid contact with skin, eyes and clothing. For external use only. Use good personal hygiene practices. Wash hands before eating, drinking, or using toilet facilities. Promptly remove soiled clothing and wash before reuse. Shower after work using plenty of soap and water.

Storage: Keep in original tightly closed containers. Keep away from heat, sparks, and open flame.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection : Wear safety glasses with side shields (or goggles).

Skin Protection : Wear resistant gloves. Glove materials may include polyvinyl chloride (PVC), neoprene or rubber.

Footwear : Wear adequate working boots.

Clothing : Wear adequate working clothes.

Respiratory Protections : Wear organic cartridges respirator.

Engineering Controls : Provide sufficient mechanical (general and/or local exhaust) ventilation.

Other : Eye bath and safety shower.

Exposure limits:

| <u>Ingrédient</u> | <u>CAS</u> | <u>TLV</u> | <u>CL₅₀</u> | <u>DL_{50<}</u> |
|---|------------|------------|------------------------|----------------------------|
| Hydrotreated light petroleum distillate | 64742-47-8 | 100 mg/m | Pas disponible | >5000mg/kg |
| White mineral oil | 8042-47-5 | 5 mg/m | >2000mg/kg | >2000mg/kg |

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

| | | | |
|-----------------------------------|---------------|--------------------------|-----------------|
| State : | Liquid | Appearance : | Opaque, viscous |
| Color : | Yellow | Odor : | chemical |
| Vapor pressure (mm Hg) : | Not available | pH : | 8.7 |
| Specific vapor density (Air=1) : | Not available | Specific gravity (25°C): | g/ml |
| Evaporation rate (Water=1) : | Not available | Boiling point (°C) : | Not available |
| Solubility in water (% p/p) : | Dispersion | Melting point (°C) : | Not available |
| Solubility in ethanol : | Not available | Viscosity (cps) : | Not available |
| Volatiles (% p/p) : | Not available | Molecular weight : | Not applicable |
| Partition coefficient water/oil : | Not available | Chemical formula : | Not applicable |

SECTION 10 : STABILITY AND REACTIVITY

| | |
|----------------------------|--------------------------------------|
| Hazardous polymerization : | Will not occur. |
| Hazardous decomposition : | May form: Nitrogen and carbon oxides |
| Chemical stability : | Stable under normal conditions. |
| Materials to avoid : | Strong oxidizing agents. |

SECTION 11 : TOXICOLOGICAL INFORMATION

| | |
|-------------------------------|--|
| Effects of chronic exposure : | Not available |
| Carcinogenicity : | Not available |
| Reproductive toxicity : | Not available |
| Teratogenicity : | Not available |
| Mutagenicity : | Not available |
| Primary Route(s) of Entry : | Skin contact, eye contact, inhalation and ingestion. |

SECTION 12 : ECOLOGICAL INFORMATION

| | |
|--------------------------------------|--|
| Environmental toxicity information : | This material has not been tested for environmental effects. |
| BOD ₅ : | Not available |
| COD : | Not available |

SECTION 13 : DISPOSAL CONSIDERATIONS

| | |
|--------------------------------|---|
| Waste Management Information : | Dispose in accordance with municipal, provincial and federal regulations. |
|--------------------------------|---|

SECTION 14 : TRANSPORT INFORMATION

| |
|----------------------|
| US DOT Information : |
| TDG Classification : |
| UN/NA Number : |
| Packaging group : |

Shipping name :

Article 1.33 (TMD), THIS Product may be no reglemented. Falsh point above 37,5°C (exemption flammable liquid)

SECTION 15 : REGULATORY INFORMATION

Canada (WHMIS) :

B3, D2B

CPR compliance :

This product has been classified in accordance with the hazard criteria of the *Controlled Products Regulations* and the MSDS contains all information required by *Controlled Products Regulations*.

SECTION 16 : OTHER INFORMATION

Emission date:

April 05th, 2013

Prepared by :

Hygienex Laboratory inc.

Phone :

(514) 522-2332

Disclaimer :

Information for this material safety data sheet was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the mandatory requirements of WHMIS. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this form. Last page.