

MATERIAL SAFETY DATA SHEETS

SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name:

Chemical name and synonyms:

Manufacturer: Laboratoire Hygienex Inc.

SILVERWAX 65

Not applicable (mixture)

Same

Address: 6400 Zéphirin-Paquet

Québec (Qc) G2C 0M3

Telephone: 1-418-522-2332 Telephone: Same

Emergency phone (CANUTEC): (613) 996-6666

Issue by: Laboratoire Hygienex Inc.

Product use: Engine cleaner

(Industrial/Institutional)

HMIS Rating:

Health: 1 Flammability: 2

Reactivity: 0
Personal protection: B

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

 $\frac{\text{Ingredient}}{\text{ESSENCES MINERALES; naphte aliphatiques}} \qquad \frac{\text{CAS}}{8052\text{-}41\text{-}3} \qquad \frac{\% \text{ p/p}}{60-100}$

2-Butoxy-1-ethanol 111-76-2 1-5

Exposure limit informations: see Section 8

SECTION 3: HAZARDS IDENTIFICATION

Eyes contact: Direct contact may cause irratation.

Skin contact: May cause skin irritation.

Inhalation: May cause dizziness and euphoria leading to unconsciousness in

severe cases. Vapors also irritate the respiratory tract. Symptoms may include coughing, difficult breathing and chest pain. A central

nervous system depressant.

Oral: Ingestion may cause lung edema.

Effects of repeated overexposure

Skin: Prolonged or repeated exposure may cause skin irritation, even skin

dryness.

Inhalation: Repeated inhalatation may cause irritation the respiratory tract..

Oral: Swallowing large amounts may cause a gastrointestinal irritation,

1...... 4. 4. ... 44.... 4

burns to mouth and throat.

Primary route of exposure: Skin contact, eye contact and inhalation are the primary routes of

exposure to this product.

The above listed potential effects of overexposure are base on actual data, results of studies performed upon similar compositions, component data, and/or expert review of the product. Please refer to section 11 for detailed toxicology information.

SECTION 4: FIRST-AID MEASURES

Eyes contact: Flush eyes gently with water for at least 15 minutes while holding

eyelids apart, occasionally lifting upper and lower lids. Get medical

attention at once.

Skin contact: In case of contact, immediately flush skin with plenty of water for at

least 15 minutes while removing contaminated clothing and shoes.

Wash clothing before reuse. Seek medical attention.

Inhalation: Remove in fresh air. Get medical attention at once.

Swallowing: Give water. Do not induce vomiting. If individual is drowsy or

unconscious, do not give anything by mouth; place individual on the left side with the head down. If possible, do not leave individual

unattended. Seek medical attention.

Notes to physicians: Treat according to person's condition and specifics of exposure.

SECTION 5: FIRE-FIGHTING MEASURES

T.D.G. Flammable class: Class 3

Flammability: Flammable liquid

Flash point, closed cup (°C): 42

Explosive limit temperature (°C): Not available Autoignition temperature (°C): Not available Lower flammable limit (% by vol.): Not available Higher flammable limit (% by vol.): Not available Sensitivity to static discharge: Not available

Sensitivity to impact: None

Hazardous Products of Combustion : May form: carbon and nitrogen oxide.

Fire and Explosion Hazards: Vapours form from this product and may travel or be moved by air

currents and ignited by pilot lights, other flames, sparks, heaters, electrical equipement, static discharges or other ignition sources at

locations distant from handling point.

Extinguishing Media: Regular foam, water, carbon dioxide.

Fire Fighting Instructions: Wear a self-contained breathing apparatus with a full face piece

operated in the positive pressure. Refer to the personal protective

equipment section of this MSDS.

SECTION 6: ACCIDENTAL RELEASE MEASURES

General information: Use proper personal protective equipment as indicated in Section 8.

Sections 13 and 15 of this MSDS provide information regarding

certain federal and state requirements.

Small spill: Remove source of heat, sparks or flames. Absorb residue or small

spills with absorbent material.

Large Spill: Stop leak if without risk. Provide adequate ventilation and

protective equipment. Remove sources of heat, sparks or flames. Spill should be collected in suitable containers or absorbed on a

suitable absorbent material for subsequent disposal.

Disposal measures: See Section 13.

SECTION 7: HANDLING AND STORAGE

Handling: Keep away from heat, sparks, and open flamme. Keep container

closed when not use. Use adequate ventilation. Avoid breathing vapours. Avoid contact with skin, eyes and clothing. For external use only. Use good personal hygiene practices. Wash hands before eating, drinking, or using toilet facilities. Promptly remove soiled clothing and wash before reuse. Shower after work using plenty of

soap and water.

Storage: Keep in original tightly closed containers. Keep away from heat,

sparks, and open flamme.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection: Wear safety glasses with side shields (or goggles).

Skin Protection: Wear resistant gloves. Glove materials may include polyvinyl

chloride (PVC), neoprene or rubber.

Footwear: Wear adequate working boots.
Clothing: Wear adequate working clothes.
Respiratory Protections: Wear organic cartriges respirator.

Engineering Controls: Provide sufficient mechanical (general and/or local exhaust)

ventilation.

Other: Eye bath and safety shower.

Exposure limits:

 $\frac{\text{Engredient}}{\text{Ingredient}} \qquad \qquad \frac{\text{CAS}}{\text{ED}_{50}} \qquad \frac{\text{ED}_{50}}{\text{ED}_{50}}$

Poly(oxy-1,2-ethanediyl), .alpha.-(nonylphenyl)-.omega.-hydroxy-

9016-45-9 Not available Not available $1.3g/kg^{(1)}$ 2-Butoxy-1-ethanol 111-76-2 Not available $450ppm/4h^{(1)}$ $1.2g/kg^{(2)}$ Stoddard solvant 8052-41-3 Not available Not available $>5g/kg^{(1)}$

 $>3g/kg^{(3)}$

(1) Oral – rat

(2) Oral – mouse

(3) Cutaneous – rabbit

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

State :LiquidAppearance :ClearColor :PinkOdor :SolvantVapor pressure (mm Hg) :Not availablepH :Not applicable

Specific vapor density (Air=1): Not available Specific gravity (25°C):0.80

Evaporation rate (Water=1): Not available Boiling point (°C): Not available Solubility in water (% p/p): Melting point (°C): Dispersion Not available Solubility in ethanol: Not available Viscosity (cps): Not available Volatiles (% p/p): Molecular weight: Not applicable Partition coefficient water/oil: Not available Chemical formula: Not applicable

SECTION 10: STABILITY AND REACTIVITY

Hazardous polymerization: Will not occur.

Hazardous decomposition: May form: Nitrogen and carbon oxdes Chemical stability: Stable under normal conditions.

Materials to avoid: Strong oxidizing agents.

SECTION 11: TOXICOLOGICAL INFORMATION

Effects of chronic exposure: Not available Carcinogenicity: Not available Reproductive toxicity: Not available Teratogenicity: Not available Mutagenicity: Not available

Primary Route(s) of Entry: Skin contact, eye contact and inhalation.

SECTION 12: ECOLOGICAL INFORMATION

Environmental toxicity information: This material has not been tested for environmental effects.

 BOD_5 : Not available COD: Not available

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Management Information: Dispose in accordance with municipal, provincial and federal

regulations.

SECTION 14: TRANSPORT INFORMATION

US DOT Information: 3 TDG Classification: 3

UN/NA Number: UN1993 Packging group: III

Shipping name: FLAMMABLE LIQUID N.O.S. (STODDARD SOLVANT)

SECTION 15: REGULATORY INFORMATION

Canada (WHMIS): B3, D2B

CPR compliance: This product has been classified in accordance with the hazard

criteria of the Controlled Products Regulations and the MSDS contains all information required by Controlled Products

Regulations.

SECTION 16: OTHER INFORMATION

Emission date: April 21th, 2012

Prepared by: Hygienex Laboratory inc.

Phone: (418) 522-2332

Disclaimer:

Information for this material safety data sheet was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the mandatory requirements of WHMIS. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this form. Last page