

CLEAR SEALANT – AEROSOL (BATCH #14345 AND LATER)

ZIEBART PART #300100

Product Description:
CLEAR AEROSOL SEALANT

Safety Data Sheet

Section 1: Manufacturer Identification

Manufactured for:	Formula # 20N022N14	
Ziebart International Corporation	Chemtrec 24-hour Emergency	(800) 424-9300
1290 East Maple Rd.	Chemtrec Foreign Emergency	(703) 527-3887
Troy, MI 48083 USA	Product Information Phone Number:	(262) 251-6180

Date MSDS Printed & Reviewed: 01/15/15

Last Formula Revision Date: 10/29/14

Section 2: Composition/Information on Ingredients

#	COMPONENT	CAS#	% by WT.	SARA 313	LISTED CARCINOGEN BY:		
				LISTED	NTP	IARC	OSHA
1	ALIPHATIC HYDROCARBON	64742-88-7	26-30	N	N	N	N
2	HEPTANE	64742-49-0	24-27	N	N	N	N
3	PROPANE	74-98-6	15-18	N	N	N	N
4	N-BUTANE	106-97-8	6-9	N	N	N	N
	NON-HAZARDOUS INGREDIENTS	N/A	20-22	N/A	N/A	N/A	N/A
TOTAL			100				

Section 3: Hazards Identification

Emergency Overview: DANGER! Extremely Flammable. Contents Under Pressure.

Appearance/Odor: Spray Mist / Solvent Odor

Potential Health Effects: See Section 11 for more information.

Likely Routes of Exposure: Eye contact, skin contact, ingestion, and inhalation

Eye: Contact may cause redness, irritation, tearing, and blurred vision

Skin: Contact may dry skin causing cracks and irritation

Ingestion: May be harmful if swallowed

Inhalation: Exposure to high concentrations of vapors may cause drowsiness, breathing difficulty, respiratory irritation, or headaches. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Medical Conditions Aggravated by Exposure:

Asthma and other respiratory ailments.

Target Organs: Kidney Liver Lung Brain

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Section 4: First Aid Measures

Eye Contact: Immediately flush eyes with water for at least 15 minutes. If irritation develops get medical attention.

Safety Data Sheet

Product Description:

CLEAR AEROSOL SEALANT

Skin Contact: Remove contaminated clothing and wash before reuse. Wash skin with soap and water. Get medical attention if irritation develops.
Inhalation: Move to fresh air. Contact emergency medical support if breathing stops or is irregular.
Ingestion: Do NOT induce vomiting. Get medical attention immediately.

Section 5: Fire Fighting Measures

Suitable Extinguishing Media: CO2 (CarbonDioxide), dry chemical, or water fog.

Unsuitable Extinguishing Media: Water spray may be unsuitable. However, if water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible explosion when exposed to extreme heat.

Products of Combustion: These products are carbon oxides (CO,CO2).

Protection of Firefighters: Full protective equipment including self-contained breathing apparatus should be used.

Section 6: Accidental Release Measures

Personal Precautions: Use personal protection recommended in Section 8.

Environmental Precautions: None known.

Methods of Containment: Absorb spilled liquid in suitable material.

Methods of Clean-up: Use spark-proof tools to sweep or scrape up and containerize.

Other Information: Ventilate the area.

Section 7: Handling and Storage

Handling:

Vapors may ignite explosively. Prevent buildup of vapors; use with adequate ventilation. Keep from sparks, heat, flame or other heat sources. Do not smoke. Turn off pilot lights, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Do not puncture or incinerate (burn) container.

Storage:

Store in dry, well-ventilated area and in accordance with federal, state, and local regulations. Do not expose to heat or store at temperatures above 120 F (48 C). Storage conditions should comply with NFPA 30B and OSHA 1910.106. If storing in cold temperatures, allow product to warm to room temperature before use.

Section 8: Exposure Controls/Personal Protection

Exposure Guidelines

#	COMPONENT	ACGIH TLV-STEL	ACGIH TLV-TWA	OSHA PEL-TWA
1	ALIPHATIC HYDROCARBON	N/E	100 ppm	500 ppm
2	HEPTANE	500 ppm	400 ppm	500 ppm
3	PROPANE	1800 ppm	2500 ppm	1000 ppm
4	N-BUTANE	N/E	800 ppm	800 ppm

Engineering Controls: Provide adequate ventilation to keep air contamination below OSHA permissible exposure limits and ACGIH TLV exposure levels.

Product Description:

CLEAR AEROSOL SEALANT

Safety Data Sheet

Eye/face Protection: Wear safety glasses with side shields. Have eye wash facilities immediately available.

Skin Protection: Chemical resistant gloves if contact is likely.

Respiratory Protection: Use NIOSH-approved air-purifying respirator with organic cartridge or canister if exposure cannot be controlled within applicable limits with ventilation.

General Hygiene Considerations: Wash thoroughly after handling.

Section 9: Physical and Chemical Properties

Color: see product description

Odor: Solvent Odor

Physical State: Aerosol - Pressurized Liquid

Freezing Point: Not Established (mixture)

Boiling Range: N.A. (Pressurized Mixture)

Flash Point: <-18C (-0.4F) c.c.

Evaporation Rate: Faster than ether

Upper Flammability Limit: Not Established (mixture)

Lower Flammability Limit: Not Established (mixture)

Vapor Pressure: Approximately 50 psig @ 10 C (70 F)

Specific Gravity, 0.712 @15 C (60 F)

Solubility (water), Negligible

VOC Percent by weight (less exempt solvents): 78.75

HAPS Percent by weight: 0

MIR Data, JU (MAXNA) MIR - 0.82

Section 10: Stability and Reactivity

Stability: Stable under normal conditions.

Conditions to Avoid: Keep away from heat, sparks, and flames.

Incompatible Materials: Strong oxidizing agents.

Hazardous Decomposition Products: by fire - Carbon Dioxide and Carbon Monoxide

Possibility of Hazardous Reactions: Will not occur.

Section 11: Toxicological Information

#	COMPONENT	LD50 Oral	LD50 Dermal
1	ALIPHATIC HYDROCARBON	N/E	N/E
2	HEPTANE	N/E	N/E
3	PROPANE	1000 mg/kg	1800 mg/kg
4	N-BUTANE	N/E	N/E

See Section 3 for other acute effect information.

Chronic Effects: Prolonged over-exposure to solvent ingredients in Section 2 may cause adverse effects to the liver, urinary, cardiovascular and reproductive systems. Reports have associated the repeated and prolonged occupational OVER-EXPOSURE to solvents with brain and nervous system damage. The deliberate misuse by concentrating and inhaling the vapors may be harmful or fatal.

Product Description:
CLEAR AEROSOL SEALANT

Safety Data Sheet

Carcinogenicity: See Section 2 for additional information.

Section 12: Ecological Information

No data available.

Section 13: Disposal Considerations

Do not puncture, incinerate or place container in trash compactor. Dispose of product in accordance with Federal, State, and Local regulations. Empty containers are 95% steel; recycle where allowed.

Section 14: Transportation Information

GROUND (D.O.T./49 CFR):

I.D. Number: UN1950
 Proper Shipping Name: AEROSOLS ("FLAMMABLE" is optional to add after AEROSOLS)
 Hazard Class: 2.1
 Packing Group: - (not applicable)
 Hazard Label: Limited Quantity (LTD QTY) label -- see 49 CFR 172.315
 Shipping Papers format: UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD QTY

AIR (IATA)

I.D. Number: UN1950
 Proper Shipping Name: AEROSOLS, FLAMMABLE
 Hazard Class: 2.1
 Packing Group: - (not applicable)
 Hazard Labels: LTD QTY label with "Y" in it, and Flammable Gas label
 Packing Instruction: Y203
 Shipping Papers format: UN1950, AEROSOLS, FLAMMABLE, 2.1

WATER (IMDG)

I.D. Number: UN1950
 Proper Shipping Name: AEROSOLS
 Hazard Class: 2.1
 Hazard Label: LTD QTY label (see IMDG 3.4.5.1)
 Packing Instruction: P003, LP02
 EmS: F-D, S-U
 Stowage and Segregation: Category A
 Shipping Papers format: UN1950, AEROSOLS, 2.1, (-18 C c.c.), LTD QTY
 No component of this product is a listed Marine Pollutant (49 CFR 172.101, Appendix B).

Section 15: Regulatory Information

International Chemical Inventory

All components of this product are listed on or exempt from the following inventories:
 TSCA (United States), CEPA/DSL (Canada), AICS (Australia), IECSC (China)

Section 313 Toxic Chemicals; See Section 2. Chemicals marked with a "Y" are subject to the SARA reporting requirements under 40 cfr 372.45 (c) (5).

Section 16: Other Information

Hazard Scale: 0=minimal, 1=slight, 2=moderate, 3=serious, 4=severe
 HMIS (American Coatings Association's Hazardous Material Identification System):

Product Description:
CLEAR AEROSOL SEALANT

Safety Data Sheet

Health = 2 Flammability = 4 Physical Hazard = 1 Personal Protection (PPE) = X

NFPA 704(National Fire Protection Association's Hazard Identification ratings system):

Health = 2 Flammability = 4 Instability = 1 Special Hazard = N/A

This MSDS is based on information believed to be reliable and accurate. Because of changing reporting requirements and other variables it is impossible to guarantee the accuracy of the information contained in this document. It is the responsibility of the user to determine proper personal protection based on the actual Condition of use and to comply with all Federal, State and Local laws and regulations.