SAFETY DATA SHEET

Page 1

Ziebart International Corporation 1290 E, Maple Road, Troy, Michigan 48083 248-837-4030

PRODUCT: 2606N-10-002/2 Z300101 SEALANT-BLACK AEROSOL 14OZ

PRIOR TO BATCH #30114







Section 01: CHEMICAL PI	RODUCT	AND COMPANY	IDENTIFICATION
-------------------------	--------	-------------	----------------

MANUFACTURED FOR ZIEBART INTERNATIONAL CORPORATION

1290 EAST MAPLE ROAD

TROY, MI 48083 USA

2606N-10-002/2 Z300100 SEALANT-CLEAR 140Z

PRODUCT NAME.....CHEMICAL FAMILY.... MIXTURE.

NOT APPLICABLE. MOLECULAR WEIGHT..... CHEMICAL FORMULA..... NOT APPLICABLE.

TRADE NAMES & SYNONYMS..... 2606N-10-002/2 Z300100 SEALANT-CLEAR 14OZ

RECOMMENDED PRODUCT USES..... RUSTFROOFING SEALANT.

FORMULA/LAB BOOK #..... F 10-606A.

Section 02: COMPOSITION/INFORMATION INGREDIENTS

Components	%	Exposure Limit	C.A.S. #	LD/50, Route, Species	LC/50 Route, Species
PETROLEUM DISTILLATES (MEDIUM ALIPHATIC SOLVENT NAPHTHA – PETROLEUM)	15 – 40	100 ppm	64742-88-7	6216 mg/kg ORAL - RAT	14.1 mg/l (4 hr) INHAL - RAT
HEXANE	30 -60	50 ppm	110-54-3	25,000 mg/kg ORAL – RAT	48,000 mg/kg INHAL – MOUSE
VM&P NAPHTHA	7 - 13	300 ppm	64742-89-8	NOT AVAILABLE	3400 ppm (4 hr) INHAL - RAT
ISOBUTANE	5 – 10	1000 ppm	75-28-5	NOT APPLICABLE	142,500 ppm (4h) INAHL - RAT
PROPANE	7 - 15	1000 ppm	74-98-6	>5000 mg/kg DERMAL-RABBITS	NOT AVAILABLE

Section 03: HAZARDS IDENTIFICATION

ROUTE OF ENTRY:

INGESTION..... MAY CAUSE HEADACHE, NAUSEA, VOMITING AND WEAKNESS.

INHALATION OF SOLVENTS MAY CAUSE IRRITATION. PROPELLANT IS A SIMPLE

ASPHYXIANT.

EYE CONTACT.

MAY CAUSE IRRITATION.
MAY BE ABSORBED BY THE SKIN.
DUST OR VAPORS MAY BE IRRITATING. SKIN ABSORPTION.....

SKIN CONTACT.....

EFFECTS OF ACUTE EXPOSURE..... DIZZINESS, NAUSEA. IRRITATION TO SKIN & EYES. EFFECTS OF CHRONIC EXPOSURE..... SOLVENTS MAY CAUSE DEFATTING DERMATITIS

Section 04: FIRST AID MEASURES

EMERGENCY FIRST AID PROCEDURE IN CASE OF EYE CONTACT, FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR

AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION. FOR SKIN, WASH

THOROUGHLY WITH SOAP AND WATER. IF AFFECTED BY INHALATION OF VAPOUR OR SPRAY MIST, REMOVE TO FRESH AIR. IF SWALLOWED; DO NOT INDUCE

VOMITING, GET MEDICAL ATTENTION.

Section 05: FIRE FIGHTING MEASURES

AUTO IGNITION TEMPERATURE (°C). 225.

INHALATION.....

SPECIAL PROCEDURES..... WATER FROM FOGGING NOZZLES MAY BE USED TO COOL CLOSED CONTAINERS

TO PREVENT BUILD-UP IF EXPOSED TO EXTREME TEMPERATURES. FULL PROTECTIVE EQUIPMENT INCLUDING SELF CONTAINED BREATHING APPARTATUS SHOULD BE WORN IN A FIRE INVOLVING THIS MATERIAL.

FLAMMABILITY..... EXTREMELY FLAMMABLE.

IF YES, UNDER WHICH CONDITIONS?..... EXCESSIVE HEAT, SPARKS AND OPEN FLAME.

(% BY VOLUME)

Z300101 MATERIAL SAFETY DATA SHEET Page 2 PRODUCT: 2606N-10-002/2 Z300100 SEALANT-BLACK 14OZ Section 05: FIRE FIGHTING MEASURES LOWER FLAMMABLE LIMIT. 0.6. (% BY VOLUME) **EXPLOSION DATA** SENSITIVITY TO STATIC DISCHARGE... NOT APPLICABLE. SENSITIVITY TO IMPACT.......NOT APPLICABLE. HAZARDOUS COMBUSTION PRODUCTS...... HYDROCARBON FUMES AND SMOKE. CARBON MONOXIDE WHERE COMBUSTION IS INCOMPLETE. AEROSOL FLAME PROJECTION CLASSIFIED AS: >45cm BUT <100cm. FLASHBACK......YES.
FLASH POINT(°C),TAG CLOSED-CUPLOWEST KNOWN VALUE IS HEXANE @ -23C. (CONCENTRATE) Section 06: ACCIDENTAL RELEASE MEASURES LEAK/SPILL...... REMOVE ALL SOURCES OF IGNITION, USE AN INERT ABSORBENT MATERIAL, AND NON-SPARKING TOOLS. VENTILATE AREA. PREVENT FROM ENTERING A WATERCOURSE Section 07: HANDLING AND STORAGE STORAGE NEEDS...... KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAMES. ENGINEERING CONTROLS...... VENTILATION - LOCAL (MECHANICAL IF USED INDOORS ON A CONTINUOUS BASIS). HANDLING PROCEDURES AND STORÉ IN A COOL, WELL VENTILATED AREA NOT TO EXCEED 50 DEG C. **EQUIPMENT** SYNERGISTIC MATERIALS...... NONE KNOWN. Section 08: EXPOSURE CONTROLS/PERSONAL PROTECTION GLOVES/ TYPE...... WEAR CHEMICAL RESISTANT GLOVES. RESPIRATORY/TYPE...... IF USED INDOORS ON A CONTINUOUS BASIS, USE OF A CARTRIDGE TYPE RESPIRATOR (NIOSH/MSHATC 23C OR EQUIVALENT) IS RECOMMENDED. OTHER/TYPE...... NOT REQUIRED. Section 09: PHYSICAL AND CHEMICAL PROPERTIES PHYSICAL STATE......AEROSOL. APPEARANCE...... BLACK SOLVENT ODOR. ODOR. @ 20 C BOILING POINT (°C)(CONC).......69-205. EVAPORATION RATE....... GREATER THAN 1. n-BUTYL ACETATE = 1 VAPOUR DENSITY (AIR=1)..... GREATER THAN 1. (BY WEIGHT) SPECIFIC GRAVITY (LIQUID)........................0.74 – 0.78 COEFFICIENT OF WATER\OIL DIST..... NOT AVAILABLE. (BY WEIGHT). Section 10: STABILITY AND REACTIVITY HAZARDOUS PRODUCTS OF IS INCOMPLETE. CHEMICAL STABILITY: COMPATIBILITY WITH OTHER

..... STRONG OXIDIZING AGENTS.

REACTIVITY CONDITIONS?...... NOT APPLICABLE.

SUBSTANCES:

NO, WHICH ONES?..

Z300101	MATERIAL SAFETY DATA SHEET Page 3					
PRODUCT: 2606N-10-002/2 Z300100 SEALANT-BLACK 14OZ						
Section 10: STABILITY AND REACTIVITY						
NO, WHICH ONES? REACTIVITY CONDITIONS? HAZARDOUS POLYMERIZATION	STRONG OXIDIZING AGENTS. NOT APPLICABLE WILL NOT OCCUR.					
Section 11	: TOXICOLOGICAL INFORMATION					
IRRITANCY OF MATERIALSENSITIZING CAPABILITY OF MATERIAL. CARCINOGENICITY OF MATERIAL	UNKNOWN. NONE KNOWN.					
TERATOGENICITY	NO INFORMATION IS AVAILABLE AND NO ADVERSE TERATOGENIC EFFECTS ARE ANTICIPATED.					
Section 12	: ECOLOGICAL CONSIDERATIONS					
ENVIRONMENTAL	NOT AVAILABLE.					
Section	13: DISPOSAL CONSIDERATIONS					
WASTE DISPOSAL	DO NOT PUNCTURE OR INCINERATE CONTAINERS, EVEN WHEN EMPTY. DISPOSE OF IN ACCORDANCE WITH LOCAL, PROVINCIAL AND FEDERAL REGULATIONS.					
Section 14: TRANSPORTATION INFORMATION						
IMDG/IMO:	CONSUMER COMMODITY (AEROSOLS, UN1950, CLASS 2.1). CONSUMER COMMODITY/LIMITED QUANTITY. AEROSOLS, FLAMMABLE. 1950. N/A2.1.					
Section	15: REGULATORY INFORMATION					
CANADIAN REGULATIONS:						
WHMIS CLASSIFICATION						
U.S. REGULATIONS:						
HMIS RATING HEALTHHMIS RATING FLAMMABILITYHMIS RATING REACTIVITYHMIS RATING PERSONAL PROTECTIONNFPA CODE 30BSARA 313 INFORMATION:	4 SEVERE HAZARD. 0 MINIMAL HAZARD. B.					
CALIFORNIA PROPOSITION 65:	WARNING: THIS PRODUCT DOES NOT INTENTIONALLY CONTAIN ANY CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.					

MATERIAL SAFETY DATA SHEET Page 4					
0 SEALANT-BLACK 14OZ					
Section 15: REGULATORY INFORMATION					
THE FOLLOWING STATEMENT IS MADE IN ORDER TO COMPLY					
WITH THE CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986:					
CAS #: CHEMICAL NAME: . N/A.					
ALL COMPONENT OF THIS PRODUCT ARE LISTED ON THE TSCA INVENTORY. ANY					
78-80.					
on 16: OTHER INFORMATION					
THE INFORMATION ON THIS MATERIAL SAFETY DATA SHEET IS PROVIDED BY ZIEBART INTERNATIONAL CORPORATION FREE OF CHARGE. WHILE BELIEVED TO BE RELIABLE, IT IS INTENDED FOR USE BY SKILLED PERSONS AT THEIR OWN RISK. ZIEBART INTERNATIONAL CORPORATION ASSUMES NO RESPONSIBILITY FOR EVENTS RESULTING OR DAMAGES INCURRED FROM ITS USE. THE INFORMATION ON THIS MATERIAL SAFETY DATA SHEET RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED HEREIN AND DOES NOT RELATE TO USE IN COMBINATION WITH ANY OTHER MATERIAL OR IN ANY PROCESS. Regulatory Affairs					